

SPINDLE SPEEDERS

Multiplicateurs de vitesse / Schnellausfspindeln



MV-5
8.000 RPM



MV-6
10.000 RPM



MV-7
15.000 RPM
MV-7C
25.000 RPM



MV-8
20.000 RPM
MV-8C
30.000 RPM



MV-9
40.000 RPM

- > Smooth and quiet running
- > Precise and rigid
- > Very high output per tool
- > No maintenance, greased for life
- > Great rigidity and high precision
- > Maximum concentricity
- > Other clamping systems under request
- > Adaptable to any machine
- > Available with any type of taper
- > Increases tool and machine life
- > Tailor made to meet customer specifications upon request

Features / Caractéristiques / Merkmale

Model	MV-2	MV-3N	MV-4N	MV-5	MV-6	MV-7	MV-7C	MV-8	MV-8C	MV-9
RPM	4.000	5.000	8.000	8.000	10.000	15.000	25.000	20.000	30.000	40.000
	1:4	1:4	1:3,5	1:6	1:6	1:7		1:5		1:6
	ISO-50	ISO-50	ER-50 / ISO-40	ER-32	ER-25	ER-20		ER-16		ER-11
KG	160	65	36	15	7	5		2,5		3
Size	Flange	50 / 60	50 / 60	50	50	40 / 50		30 / 40 R8		30 / 40
HSK Size	Flange	-	-	100	80 / 100		63 / 80		63	63

V 1.0 We reserve the right to modify the information without prior notice.

MADAULA GROUP: Chicago, Sao Paulo, Barcelona, Bologna, Waghäusel, Annecy

Carrer de Barcelona, 146
St. Fost - Barcelona, 081

(34) 935 933 600
(34) 935 700 79

www.madaula.com
commercial@madaula.com

